


Formats / *Formatos*

80x80 cm 31"x31"



60x60 cm 24"x24"

Technical features / *Características técnicas*

description	LENGTH AND WIDTH	THICKNESS	STRAIGHTNESS OF SIDES	RECTANGULARITY	SURFACE FLATNESS	WATER ABSORPTION	BREAKING STRENGTH (N)	MODULUS OF RUPTURE (N/mm ²)	RESISTANCE TO SURFACE ABRASION OF GLAZED TILES INTENDED FOR USE ON FLOORS	RESISTANCE TO THERMAL SHOCK	CRAZING RESISTANCE	FROST RESISTANCE	CHEMICAL RESISTANCE	RESISTANCE TO STAINING
REQUIRED STANDARDS (ISO 13006)	± 0.3 %	± 5 %	± 0.3 %	± 0.3 %	± 0.4 %	E ≤ 0.5 %	1300 ≤ S	35 ≤ R	REPORT ABRASION CLASS AND CYCLES PASSED	NO CRAZING OBSERVED	NO CRAZING OBSERVED	REQUIRED	GB ≤	CLASS 3 ≤
RESULTS	<± 0.3 %	<± 5 %	<± 0.3 %	<± 0.3 %	<± 0.4 %	E ≤ 0.5 %	2400 ≤ S	45 ≤ R	CLASS 1 CYCLES 150	RESISTANT	RESISTANT	RESISTANT	GA	CLASS 4 ≤



description	LENGTH AND WIDTH	THICKNESS	STRAIGHTNESS OF SIDES	RECTANGULARITY	SURFACE FLATNESS	WATER ABSORPTION	BREAKING STRENGTH (N)	MODULUS OF RUPTURE (N/mm ²)	RESISTANCE TO SURFACE ABRASION OF GLAZED TILES INTENDED FOR USE ON FLOORS	RESISTANCE TO THERMAL SHOCK	CRAZING RESISTANCE	FROST RESISTANCE	CHEMICAL RESISTANCE	RESISTANCE TO STAINING
REQUIRED STANDARDS (ISO 13006)	± 0.3 %	± 5 %	± 0.3 %	± 0.3 %	± 0.4 %	E ≤ 0.5 %	1300 ≤ S	35 ≤ R	REPORT ABRASION CLASS AND CYCLES PASSED	NO CRAZING OBSERVED	NO CRAZING OBSERVED	REQUIRED	GB ≤	CLASS 3 ≤
RESULTS	<± 0.3 %	<± 5 %	<± 0.3 %	<± 0.3 %	<± 0.4 %	E ≤ 0.5 %	2400 ≤ S	45 ≤ R	CLASS 1 CYCLES 150	RESISTANT	RESISTANT	RESISTANT	GB	CLASS 4 ≤

Packing / *Embalaje*

FORMAT FORMATO	PCS/BOX PIEZAS/CAJA	M2/BOX M2/CAJA	M2/PALLET M2/PALÉ	BOXES/PALLET CAJAS/PALÉ	WEIGHT/PALLET PESO/PALÉ	PALLET (cm) PALÉ (cm)
80x80 cm · 31"x31"	2	1,28	61,44	48	1296	80x120x95
60x60 cm · 24"x24"	4	1,44	46,08	32	960	80x120x75

