




Formats / *Formatos*



80x80 cm 31"x31"

Technical features / *Características técnicas*

description	LENGTH AND WIDTH	THICKNESS	STRAIGHTNESS OF SIDES	RECTANGULARITY	SURFACE FLATNESS	WATER ABSORPTION	BREAKING STRENGTH (N)	MODULUS OF RUPTURE (N/mm ²)	RESISTANCE TO SURFACE ABRASION OF GLAZED TILES INTENDED FOR USE ON FLOORS	RESISTANCE TO THERMAL SHOCK	CRAZING RESISTANCE	FROST RESISTANCE	CHEMICAL RESISTANCE	RESISTANCE TO STAINING
REQUIRED STANDARDS (ISO 13006)	± 0.3 %	± 5 %	± 0.3 %	± 0.3 %	± 0.4 %	E ≤ 0.5 %	1300 $\leq$ 5	35sR	REPORT ABRASION CLASS AND CYCLES PASSED	NO CRAZING OBSERVED	NO CRAZING OBSERVED	REQUIRED	GBs	CLASS 3 s
RESULTS	<± 0.3 %	<± 5 %	<± 0.3 %	<± 0.3 %	<± 0.4 %	E ≤ 0.5 %	2400 $\leq$ 5	45sR	CLASS 2 CYCLES 600	RESISTANT	RESISTANT	RESISTANT	GA	CLASS 4 s

description	LENGTH AND WIDTH	THICKNESS	STRAIGHTNESS OF SIDES	RECTANGULARITY	SURFACE FLATNESS	WATER ABSORPTION	BREAKING STRENGTH (N)	MODULUS OF RUPTURE (N/mm ²)	RESISTANCE TO SURFACE ABRASION OF GLAZED TILES INTENDED FOR USE ON FLOORS	RESISTANCE TO THERMAL SHOCK	CRAZING RESISTANCE	FROST RESISTANCE	CHEMICAL RESISTANCE	RESISTANCE TO STAINING	slip-resistance (flat surface PEDINULUM BS 7270)
REQUIRED STANDARDS (ISO 13006)	± 0.3 %	± 5 %	± 0.3 %	± 0.3 %	± 0.4 %	E ≤ 0.5 %	1300 $\leq$ 5	35sR	REPORT ABRASION CLASS AND CYCLES PASSED	NO CRAZING OBSERVED	NO CRAZING OBSERVED	REQUIRED	GBs	CLASS 3 s	-
RESULTS	<± 0.3 %	<± 5 %	<± 0.3 %	<± 0.3 %	<± 0.4 %	E ≤ 0.5 %	2300 $\leq$ 5	43sR	CLASS 3 CYCLES 1500	RESISTANT	RESISTANT	RESISTANT	GA	CLASS 4 s	Low slip potential (36+)

Packing / *Embalaje*

FORMAT FORMATO	PCS/BOX PIEZAS/CAJA	M2/BOX M2/CAJA	M2/PALLET M2/PALÉ	BOXES/PALLET CAJAS/PALÉ	WEIGHT/PALLET PESO/PALÉ	PALLET (cm) PALÉ (cm)
80x80 cm · 31"x31"	2	1,28	61,44	48	1296	80x120x95

