




Formats / *Formatos*



29x29 cm 11,8"x11,8"

Technical features / *Características técnicas*

description	LENGTH AND WIDTH	THICKNESS	STRAIGHTNESS OF SIDES	RECTANGULARITY	SURFACE FLATNESS	WATER ABSORPTION	BREAKING STRENGTH (N)	MODULUS OF RUPTURE (N/mm ²)	RESISTANCE TO SURFACE ABRASION OF GLAZED TILES INTENDED FOR USE ON FLOORS	RESISTANCE TO THERMAL SHOCK	CRAZING RESISTANCE	FROST RESISTANCE	CHEMICAL RESISTANCE	RESISTANCE TO STAINING
REQUIRED STANDARDS (ISO 13006)	± 0.6 %	± 5 %	± 0.5 %	± 0.5 %	± 0.5 %	E ≤ 0.5 %	700 ≤S	35≤R	REPORT ABRASION CLASS AND CYCLES PASSED	NO CRAZING OBSERVED	NO CRAZING OBSERVED	REQUIRED	GB≤	CLASS 3 ≤
RESULTS	<± 0.4 %	<± 5 %	<± 0.5 %	<± 0.5 %	<± 0.5 %	E ≤ 0.5 %	850 ≤S	45≤R	CLASS 2 CYCLES 600	RESISTANT	RESISTANT	RESISTANT	GA	CLASS 4 ≤

Packing / *Embalaje*

FORMAT FORMATO	PCS/BOX PIEZAS/CAJA	PCS/M2 PIEZAS/M2	M2/BOX M2/CAJA	WEIGHT/BOX PESO/CAJA	M2/PALLET M2/PALÉ	BOXES/PALLET CAJAS/PALÉ	WEIGHT/PALLET PESO/PALÉ	PALLET (cm) PALÉ (cm)
29x29 cm · 11,8"x11,8"	19	~12	1.5979	19.9	115.0488	72	1911	80x120x102

